



Notes:

- 1>Type:Film to Glass
- 2.Operating Voltages: $\leq 10V$
- 3.Operating Temperature: $-20^\circ C \sim 65^\circ C$
- Storage Temperature: $-30^\circ C \sim 70^\circ C$
- 4.Life Time:1,000,000 times
- 5.Connected Material:FPC
- 6.Response Time: $\leq 10ms$
- 7.Linearity: $\leq 1.5\%$
- 8.Transmittance: $\geq 75\%$
- 9.Surface Hardness: $\geq 3H(\text{penicil})$
- 10.Operation force: $80g \sim 150g$

11.Resistance: $50\Omega < \text{PIN1, PIN2} < 250\Omega$

- $50\Omega < \text{PIN2, PIN4} < 250\Omega$
- $50\Omega < \text{PIN4, PIN6} < 250\Omega$
- $50\Omega < \text{PIN5, PIN1} < 250\Omega$

TOLERANCES
(UNLESS OTHERWISE STATED)
DIMENSIONS ANGLES $\pm 0.5\%$

>2000MM	$\pm 2.0MM$
1600- X- 5300MM	$\pm 1.2MM$
1200- X- 5180MM	$\pm 0.8MM$
800- X- 5120MM	$\pm 0.5MM$
400- X- 580MM	$\pm 0.2MM$
120- X- 540MM	$\pm 0.2MM$
30- X- 512MM	$\pm 0.1MM$

格域触控
GreenTouch

GreenTouch Technology Co.,Ltd

Model No.:	GT-89-10A-1	Size	10.4"	Ratio	16:9
Structure	GT-C	Unit	mm	Scale	1:1
Design	2015	Date	2015.6.5	Page	1/1
Check	11/15	Date	2015.6.5	Version	1.0
Released	ESB	Date	2015.6.5		